


# F.J. MOORE

MFG. CO.

500 Washington Street West  
Cannon Falls, MN 55009  
(800) 658-2331 Fax (507) 263-4439

[www.fjmooremfg.com](http://www.fjmooremfg.com)



## PRODUCT DATA SHEET

### No.22 High Pitch - Copper

#### DESCRIPTION

- ◆ Frost resistant design prevents vent closure.
- ◆ Patented two piece telescopic cover-all design provides complete enclosure of DWV pipe and roof penetration point.
- ◆ Permanent three point seal unaffected by daily roof movement and structure settling.
- ◆ No.2 style, flat profile lead top, forms to DWV pipe I.D.
- ◆ Prestamped, base flashing raised bosses permanently seal at nailing points.
- ◆ Installs without removal or alteration of existing shingle pattern fits all architectural and 3 tab shingles.
- ◆ Suitable for new construction, tear-off and retrofit.
- ◆ Retrofits over many existing flashings.
- ◆ Impervious to all extreme weather and storm conditions.
- ◆ 10 Year warranty when properly installed.



#### PHYSICAL PROPERTIES

- ◆ 16 oz. Copper.
- ◆ Lead cap stamped 2-1/2 lb. chemical sheet, 99.6% pure.
- ◆ Flat profile top (No.2 style).

Product Code	DWV Pipe	Pitch Range	Base Length	Base Width	Top Height	Sleeve Travel
2" No. 22 SM - C	2"	5/12 - 15/12	12.5"	10.3"	7"	1 - 3"
3" No. 22 SM - C	3"	5/12 - 15/12	13.7"	12"	7"	1 - 3"
4" No. 22 SM - C	4"	5/12 - 15/12	16.2"	15"	7"	1 - 3"
5" No. 22 SM - C	5"	5/12 - 15/12	18.3"	16"	7"	1 - 3"

#### INSTALLATION

1. Cut vent pipe approximately 2" above top of base sleeve to allow for roof movement (expansion and contraction).
2. Place flange on roof beside vent pipe to adjust exact pitch. Use hip corners to increase or decrease pitch.
3. Place flange over pipe, rotate under at least one row of shingles.
4. Center base sleeve around DWV pipe so there is approximately 1" of air space around perimeter.
5. Install top sleeve. Tighten ring clamp.
6. Nail base flashing to roof.

#### HANDLING NOTES

- ◆ Avoid sources of physical damage during handling and transporting.
- ◆ Material Safety Data Sheet available upon request.